

4RM

Case sealing solutions for Random cartons



Optional No/ Low Tape indicator reduces changeover downtime



Optional MS/ Polycarbonate Safety Guards for Operator's safety.

Features and benefits

- Automatic Sealing of Random Size Cartons
- Machine automatically adjust itself to varying size cartons
- Best suited for random sealing of Tall & Heavy Cartons
- Independently controlled top & bottom drives ensures smooth flow of heavy cartons
- Ideal for integrating with different production lines
- Auto on /off enables power saving during idle time
- Twin mast column for greater stability during operation
- Uniform & controlled pressure during taping
- Pneumatically controlled top drive & side guides align with the carton width & height automatically
- Belt speed of 20 m/minute as per international norms

4RM

Case sealing solutions for Random cartons

Technical Specifications:

Machine Specification	4RM
Taping Head	2"/2.5"/3"
Length	1080 mm
Width	570 mm
Height	1385 mm
Weight	159 Kg
Color	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive Motor	0.25 HP, 2 No.
Belt speed	20 Mtrs/ Min
Machine Through put	Up to 16 Cartons/ Min (Depending on Length)
Utility Requirements	
Air Requirement	6 Bar
Air Consumption	9.5 Litres/ Cycle
Power Supply	415 V AC, 3 Phase, 50 Hz
Power Consumption	0.4KW
Tap Roll Length	65 M/ 650 M/ 1000 M
Case Dimensions	
Length	150 mm - Unlimited
Width	160 mm -450 mm
Height	100 mm -400 mm
Weight	2- 15 Kg
Carton Ply	Min 3 Ply

 **SIGNODE**[®]

Your partner in industrial packaging world wide

E: info@signodeindia.com | W: www.signodegroup.com

Toll Free Number for Services 1800 419 1466

Signode has a policy of continuous product development and reserves the right to alter specifications at any time without prior notice