

5FRM

Fully Automatic Random Case Sealer with Four flap closure



New Flexible 'Soft' taping head with Variable tape overlap up to 75mm



Optional No/ Low Tape indicator reduces changeover downtime



Optional MS/ Polycarbonate Safety Guards for Operator's safety.

Features and benefits

- Automatic Sealing of Random Size Cartons
- Machine automatically adjust itself to varying size cartons
- Independently controlled top and side drives ensures smooth flow of cartons
- Ideal for integrating with different production lines
- Auto on /off feature enables power saving during idle time
- Twin mast column for greater stability during operation
- Pneumatically controlled top drive & side guides align with the carton width & height automatically
- Uniform & controlled pressure during taping
- Belt speed of 18 m/minute as per international norms
- Optional MS(Wiremesh) or Polycarbonate safety guards for operator safety.

5FRM

Fully Automatic Random Case Sealer with Four flap closure

Technical Specifications

Machine Specification	5FRM-Standard	5FRM-Small
Taping Head Type	Flexible-2"/2.5"/3"	Flexible-2"/2.5"/3"
Length	2040 mm	1470 mm
Width	960 mm	700 mm
Height	1450 mm	1350 mm
Weight	295 Kg	255 Kg
Color	RAL 6000 & RAL 1021 Yellow (Moving Parts)	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive Motor	0.25 HP, 3 No.	0.25 HP, 3 No.
Machine Through put	5-7 carton/min	8-9 carton/min
Utility Requirements		
Air Requirement	6 Bar	6 Bar
Air Consumption	15.8 Litres/ Cycle	8.6 Litres/Cycle
Power Supply	415 V AC, 3 Phase, 50 Hz	415 V AC, 3 Phase, 50 Hz
Power Consumption	0.6 KW	0.4 KW
Tap Roll Length	65 M/ 650 M/ 1000 M	65 M/ 650 M/ 1000 M
Case Dimension		
Length	200- 570 mm	200- 400 mm
Width	170-450 mm	130-320 mm
Height	150-400 mm	130-310 mm
Weight	7-40Kg	7-40Kg
Carton Ply	5 Ply	5 Ply

 **SIGNODE**[®]

Your partner in industrial packaging world wide

E: info@signodeindia.com | W: www.signodegroup.com

Toll Free Number for Services 1800 419 1466

Signode has a policy of continuous product development and reserves the right to alter specifications at any time without prior notice